

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE  
LAUNCH SHOCK APPLICATIONS  
Inventor: CUONG TU HUA  
Docket No.: 2739-002

1 / 12




FIG. 1

(Prior Art)

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE  
LAUNCH SHOCK APPLICATIONS  
Inventor: CUONG TU HUA  
Docket No.: 2739-002

2 / 12




FIG. 2

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE  
LAUNCH SHOCK APPLICATIONS  
Inventor: CUONG TU HUA  
Docket No.: 2739-002

3 / 12




FIG. 3

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE  
LAUNCH SHOCK APPLICATIONS  
Inventor: CUONG TU HUA  
Docket No.: 2739-002

4 / 12




FIG. 4




FIG. 5

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE

LAUNCH SHOCK APPLICATIONS

Inventor: CUONG TU HUA

Docket No.: 2739-002

6 / 12

Timing Diagram  
(Relationship Between Three Clock Rates)




FIG. 6

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE  
LAUNCH SHOCK APPLICATIONS

Inventor: CUONG TU HUA

Docket No.: 2739-002

7 / 12

Projectile Velocity, Deficit Velocity, and Correction Velocity  
(Calculated with respect to an Inertial Frame of Reference)




FIG. 7

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE

LAUNCH SHOCK APPLICATIONS

Inventor: CUONG TU HUA

Docket No.: 2739-002

8 / 12




FIG. 8

MULTI-SENSOR GUIDANCE SYSTEM FOR EXTREME FORCE

LAUNCH SHOCK APPLICATIONS

Inventor: CUONG TU HUA

Docket No.: 2739-002

9 / 12




FIG. 9




FIG. 10




FIG. 11




FIG. 12